

USA CUSTOMER SERVICE

Olight Support P.O. BOX 4010 Marietta, GA 30060 Tel: 770 627 4714 Open hours: 10:00 a.m. – 7:00 p.m. EST Mon-Fri Service support:

techsupport@olightworld.us cs@olightworld.us

GERMANY CUSTOMER SERVICE

Olight Support kontakt@olightgemany.de

CHINA HEADQUARTERS

Olight Technology Co., Ltd.

5th Floor, Building A2, Fuhai Information Harbor, Fuyong town, Bao'an District, Shenzhen, China Post code:518103 Tel:+86-755-8145 2518 / 8145 2618

Fax:+86-755-8145 2508

Open hours: Monday-Friday 9:00a.m - 18:00p.m Service support: customer-service@olightword.com (Europe, Middle East, West Asia, Asia Pacific and China)











/olightworld

O OLIGHT'





MAKING A DIFFERENCE

WHO WE ARE

WE HAVE ONE SIMPLE GOAL: TO PUT AN OLIGHT IN AS MANY PEOPLE'S HANDS AS POSSIBLE.

Why? Because we believe that no one should be left in the dark — period. We believe that everyone should have a quality illumination source when it matters most. We care about every little detail from brightness to runtime to ergonomics, size and weight — and more importantly, how we can improve your life with light. We want to push our products to the limit so that we can give you the best lights in the smallest package possible for the best price, so you have the right tools to conquer the night.

We are a global technology driven lighting company filled with dedicated people who want to provide the best for our customers. We are Outdoorsmen, Sportsmen, Veterans, and DIY go-getters — we are you. We use our own products everyday to make sure we practice what we preach; it keeps us honest. We want to give you quality design and functionality that really works when you need it to. We are just a group of people looking to change the world one light at a time. And we want you to be a part of it.

ALL OLIGHT FLASHLIGHT PRODUCTS ARE TESTED TO ANSI/NEMA FL1-2009 STANDARDS.

OUR HISTORY

OLIGHT WAS ESTABLISHED IN 2006 AS A MANUFACTURER OF HIGH QUALITY ILLUMINATION TOOLS.

After breaking out in the outdoor and flashlight enthusiast markets in Europe, Olight turned its focus on to the tactical market and began designing products tailored to meet the needs of law enforcement and government agencies. Our M series lights pushed the envelope of light output, features, and durability, solidifying our reputation and position in the marketplace. Not content to rest on our laurels, we continued to innovate with our powerful SR line of searchlights, the super compact S Baton series, and the X7 Marauder. Our product line has expanded to include models powered by CR123A lithium batteries, standard AAA and AA alkaline batteries, and convenient rechargeable battery packs. We continue to deliver cutting-edge products and are committed to keeping Olight a forerunner in the illumination tool market — providing products that are accessible to everyone. We believe that, with your support, our future will be brighter than ever.

i3E EOS (Gift Box Edition)

01-02

PAGE NUMBER

TABLE OF

S1 BATON S2 BATON S1A BATON **S2A BATON** S1R BATON S2R BATON S10R BATON III S30R BATON III

PAGE NUMBER 03-12

H1 NOVA H1R NOVA

PAGE NUMBER 17-20







SR MINI INTIMIDATOR II **SR52 UT INTIMIDATOR**

PAGE NUMBER 13-16



H-SERIES

H05 ACTIVE H05S ACTIVE H15S WAVE

M23 JAVELOT

M1X STRIKER

M2X-UT JAVELOT

M20SX JAVELOT


PAGE NUMBER 25-30

M3XS-UT JAVELOT

PAGE NUMBER 21-24

R20 JAVELOT R50 SEEKER R50 PRO / LE SEEKER

> PAGE NUMBER 31-36



R-SERIES



PL-1 II VALKYRIE

PAGE NUMBER 37-38 **SPECIFICATIONS CHART**

PAGE NUMBER

47-50

PAGE NUMBER 39-42

X7 MARAUDER

X-SERIES

SPECIFICATIONS

ACCESSORIES

QUALITY

43-46

ACCESSORIES

FROM OLIGHT

PAGE NUMBER



BEAM COMPARISON

BEAM COMPARISON CHART

PAGE NUMBER 51-52





i3E EOS (Gift Box Edition)


SINGLE-OUTPUT LED KEYCHAIN LIGHT





DESCRIPTION

The i3E EOS (Gift Box Edition) is an extremely compact flashlight with a single output of 90 lumens, all running off of a single AAA battery. The i3E flashlight features a high-performance Philips LUXEON TX LED, and a PMMA TIR lens that gives a beam distance up to 44 meters. The versatile i3E fits easily into a pocket or bag, and can be connected to a keychain without adding significant bulk to your keys, plus its slim and smooth design won't wear on your clothing or purse. The i3E is the perfect choice for a small, bright, and affordable light to take with you anywhere.

- ◆ Single brightness level with an output up to 90 lumens
- ◆ Uses TIR optics lens, giving a soft and balanced beam
- ◆ Multiple color options: red/purple/blue/green/black
- ◆ A perfect combination of tiny and mighty





























S1 BATON

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT

500 LUMENS

DESCRIPTION

The S1 Baton is the latest evolution of our most popular Baton series. At less than 2.5 inches, and just over one ounce, the S1 Baton fits easily in your pocket, making it perfect for everyday carry. While the S1 Baton is small, its TIR-focused output is a mighty 500 lumens whose beam reaches 360 feet. And it has plenty of features to be the most useful light you can own, like its magnetic tailcap, variable light settings, and automatic timer shutoff.

FEATURES

- ◆ Uses TIR optics lens, giving a soft and balanced beam
- ◆ Magnetic tailcap, pocket clip and moonlight mode
- ◆ Silicone low profile side switch
- ◆ Built-in timer
- Compact and mighty



STANDARD	MODE 1	ODE 1 MODE 2		MODE 4			
31/2	500~300 lm	80 lm	8 lm	0.5 lm			
CR123A 3V 1500mAh	1.5+90 min	6 hrs	40 hrs	25 days			
RCR123A 3.7V 650mAh	1.5+60 min	4 hrs	25 hrs	15 days			
compatible	CR123A / RCR123A (not included)						
1	1.5 meters						
шшш	(L) 2.4in / 61mm× (D) 0.83in / 21mm						
$\overline{\Omega}$	1.06 oz / 30g (excluding battery)						



950 LUMENS

STANDARD	MODE 1	MODE 2	MODE 3	MODE 4	MODE 5				
314	950~400 lm	400 lm	80 lm	10 lm	0.5 lm				
2°CR123A (3V 1500mAh)	2+100 min	165 min	12 hrs	95 hrs	35 days				
1*18650(3.6V 3400mAh)	2+170 min	245 min	19 hrs	144 hrs	60 days				
compatible	18650 or 2×CR123A / RCR123A (not included)								
	1.5 meters								
шшш	(L) 4.06in / 103mm× (D) 0.91in / 23mm								
ΔI_{∇}	1.78 oz / 5	50.5g (exc	luding bat	tery)					

FEATURES

- ◆ Uses TIR optics lens, giving a soft and balanced beam
- ◆ Magnetic tailcap, pocket clip and moonlight mode
- ◆ Silicone low profile side switch
- Built-in timer
- Compact enough for everyday use

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT

DESCRIPTION

The S2 Baton is a side switch LED flashlight powered by a single 18650 battery or two CR123A lithium batteries. The S2 uses a high performance Cree XM-L2 LED which is able to deliver a maximum output of 950 lumens. The S2 carries a balanced beam by using a 90% light transmittance PMMA TIR lens that provides the light with a cool white balanced appearance. The S2 continues to apply the same signature features as the Olight S-series flashlights including a low profile side switch, removable pocket clip, magnetic tailcap, and timer.































NEW



S1A BATON

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT





n	FS	C.R	IPT	ION
	17.4			IL-IN

Only powered by a single AA battery, the S1A Baton is the upgraded version of the popular S15 Baton, yet with double the performance. It maintains the style of Olight Baton series, such as the stainless steel pocket clip, blue clamping ring on the bezel and switch and a magnetic tailcap. It has a range of 0.5~220 lumens, yet when powered by a 14500 lithium battery, it can deliver a maximum output of 600 lumens.

FEATURES

- ◆ Uses TIR optic lens, giving a soft and balanced beam
- ◆ Magnetic tailcap, pocket clip and moonlight mode
- ◆ 100% discharge of battery, highly energy-efficient
- ◆ Built-in timer




STANDARD	MODE 1	MODE 2		MODE 3	MODE 4	MODE 5		
31/2	600~300 lm	220~100 lm		50 lm	5 lm	0.5 lm		
1*AA (1.5V Lithium Iron Battery)	/	110+30 min		10.5 hrs	80 hrs	25 days		
1*AA (1.5V Alkaline Battery)	/	12+80 min		4.5 hrs	75 hrs	20 days		
(3.7V 14500 Battery)	1+60 min	100+10 min		6.5 hrs	60 hrs	15 days		
mm.	included		1.5V 290	0mAh AA Lithium Iron battery				
шш	compatible	ļ	AA					
=	1.5 meters							
шшш	(L) 3.13in / 79.5mm× (D) 0.83in/21mm							
$\overline{\mathbb{Q}}$	1.85 oz / 52	2.5	g (includin	g battery)				



550 LUMENS

STANDARD	MODE 1	MODE 2		MODE 3	MODE 4	MODE 5		
31/2	550~260 lm	260 lm		120 lm	20 lm	0.5 lm		
2°AA (1.5V Lithium Iron Battery)	3+240 min	250 min		10 hrs	80 hrs	50 days		
2*AA (1.5V Alkaline Battery)	3+80 min	105 min		5.5 hrs	60 hrs	35 days		
шт	included		1.5V 290	0mAh AA Li	thium Iron I	pattery × 2		
ШШР	compatible	;	AA×2					
	1 meter	1 meter						
шшш	(L) 5.2in / 132mm× (D) 0.91in / 23mm							
272	3.03 oz / 8	36	g (includi	ng battery)			



S2A BATON

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT

DESCRIPTION

The S2A Baton is a compact and light weight flashlight powered by two AA batteries that delivers a maximum output of 550 lumens. The S2A Baton has a TIR optic lens that provides a soft and balanced beam for maximum visibility. The light features a slim body wrapped in a silicone gel for a confident grip available in fluorescent black, grey, blue, and yellow.

- ◆ Uses TIR optic lens, giving a soft and balanced beam
- ◆ Magnetic tailcap, pocket clip and moonlight mode
- ◆ Flashlight body wrapped with skin-safe silicone material of various colors for better hand grip
- ◆ 100% discharge of battery, highly energy-efficient
- ◆ Built-in timer









S1R BATON

RECHARGEABLE VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT



DESCRIPTION

The S1R Baton is a side-switch, rechargeable EDC flashlight, powered by one high discharge RCR123 rechargeable lithium battery giving a maximum output of 900 lumens. The light features magnetic USB charging so you will never be left in the dark.

FEATURES

- ◆ TIR optic lens, giving a soft and balanced beam
- Built-in timer
- ◆ Magnetic USB charging with included battery and cable
- ◆ Red low power indicator side switch
- ◆ Reverse polarity protection



STANDARD	TURBO S	TURBO		HIGH	MEDIUM	LOW	MOON	
31/4	900~300 lm	600~300 lm		300 lm	60 lm	12 lm	0.5 lm	
	1.5+50 min	1.5+55 min		60 min	4.5 hrs	33 hrs	15 days	
шт.	included		Cus	ustomized 550mAh 5C RCR123A				
	also comp	atible	Othe	Other RCR123A (not directly rechargeable)				
/ =	1.5 meters							
шш	(L) 2.6in / 66mm× (D) 0.83in / 21mm							
1	1.9 oz / 54g (including battery)							



1020 LUMENS


SZK BAI UNRECHARGEABLE VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT

STANDARD	MODE 1	MODE 2		MODE 3	MODE 4	MODE 5		
314	1020~500 lm	500 lm		120 lm	12 lm	0.5 lm		
(1)	2+190 min	200 min		13 hrs	120 hrs	60 days		
шть	included		Cust	Customized 3200mAh 18650				
Ш	also compa	atible		er 18650 or 2×RCR123A th not directly rechargeable)				
/	1.5 meters	1.5 meters						
шшш	(L) 4.13in / 105mm× (D) 0.91in / 23mm							
	3.58 oz / 101.5g (including battery)							

DESCRIPTION

The S2R Baton is a side-switch, rechargeable EDC flashlight, powered by one high discharge 18650 rechargeable lithium battery giving a maximum output of 1020 lumens. The light features magnetic USB charging so you will never be left in the dark.

- ◆ TIR optic lens, giving a soft and balanced beam
- Built-in timer
- Magnetic USB charging with included battery and cable
- Red low power indicator side switch
- Reverse polarity protection













STANDARD ACCESSORY: 4.2V 1000mAh Desktop Charging Dock











STANDARD ACCESSORY: 4.2V 1000mAh Desktop Charging Dock







S10R BATON III

RECHARGEABLE V



VARIABLE-OUTPUT	SIDE-SWITCH LED	FLASHLIGHT

DESCRIPTION

The S10R Baton III is the third generation of the popular flagship S10R rechargeable EDC flashlights using a single RCR123A. With a brand new LED, higher output, smaller size, timer function and improved accessories, the S10R Baton III is the perfect companion for everywhere you go.

FEATURES

- ◆ Uses the highly energy efficient SST-40 LED from Luminus
- ◆ Magnetic tailcap, pocket clip and moonlight mode
- ◆ Low battery indicator under the side switch
- ◆ Micro-USB desktop charging dock provided for fast and stable charging

STANDARD	MODE 1	М	ODE 2	MODE 3	MODE 4		
31/2	600~300 lm	12	20 lm	12 lm	0.5 lm		
()	1.5+60 min	16	60 min	33 hrs	15 days		
ППП	included		Customized 650mAh RCR123A				
шш	also compati	ble	Other RCF	R123A (not directly rechargeable)			
=	1.5 meters						
шшш	(L) 2.7in / 68.5mm× (D) 0.91in / 23mm						
	2.05 oz / 58g (including battery)						



O OLIGHT &	SIOR
Micro Dok (included for S10R III / S30R III)	Magnetic Tailcap (optional)

1050 LUMENS

The S30R Baton III is the third generation of our flagship S30R

flashlights. It uses an 18650 battery with a maximum output of

1050 lumens. The high output, portability, convenient charging,

and long runtime can meet all your illumination needs for home,

RECHARGEABLE VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT

STANDARD	MODE 1	MODE 2		MODE 3	MODE 4	MODE 5		
31/2	1050~500 lm	500 lm		120 lm	12 lm	0.5 lm		
	2+200 min	210 min		15 hrs	130 hrs	100 days		
ппп	included	С		Customized 3.6V 3500mAh 18650				
ШШ	also compat	ible		18650 or 2×RCR123A not directly rechargeable)				
=	1.5 meters							
шшш	(L) 4.49in / 114mm× (D) 0.98in / 25mm							
\mathfrak{A}	3.88 oz / 110g (including battery)							

travel, and the great outdoors.

FEATURES

DESCRIPTION

- ◆ Utilizes a smooth aluminum reflector which provides an improved beam focus for medium and close-range illumination
- ◆ Magnetic tailcap, pocket clip and moonlight mode
- ◆ Low battery indicator under the side switch
- ◆ Micro-USB desktop charging dock provided for fast and stable charging















WIDE-ANGLED VARIABLE-OUTPUT RECHARGEABLE LED FLASHLIGHT



DESCRIPTION

The SR MINI Intimidator II is the next generation of its predecessor, the SR MINI. At just over five inches in length while giving a powerful 3200 lumens max output, this upgrade showcases a compact powerhouse with a textured lens that diffuses the beam to create a wide-angled and diffused pattern, but also projects the light up to 268 meters. The soft silicone gel switch sits recessed near the head to reduce accidental activation.

FEATURES

- ◆ Maximum output of 3200 lumens on turbo mode
- ◆ Highly diffused acrylic lens creating smooth floodlight
- ◆ Quick turbo mode operation when the light is on
- ♦ Easily accessible lockout feature with triple click from side switch on off position
- ◆ Red LED indicator above Micro-USB port glows when battery power is low



STANDARD	MODE 1	MODE 2	MODE 3	MODE 4			
314	3200 lm	1600 lm	600 lm	120 lm			
(1)	/	3 hrs	8 hrs	36 hrs			
compatible	3×18650 or 6×CR123A (not included)						
	1.5 meters						
шшш	(L) 5.2in / 132mm× (D) 1.87in / 47.5mm						
$\Delta I \Delta$	6.38 oz / 181g (excluding battery)						



1100 LUMENS

EXTENDED-RANGE RECHARGEABLE LED FLASHLIGHT

STANDARD	MODE 1	MODE 2	MODE 3		
314	1100 lm	550 lm	80 lm		
(1)	4 hrs	7.5 hrs	40 hrs		
compatible	3×18650 or 6×CR123A (not included)				
/ =	1 meter				
шшш	(L) 6.3in / 161.5mm×(D) 2.48in / 63mm 14.3 oz / 405g (excluding battery)				
A					




DESCRIPTION

The SR52 UT Intimidator offers an extremely bright output and an incredible throw of 800 meters at a compact size. So whether you are playing a night football game in the desert, running a search and rescue operation, or simply lighting up the front yard, the SR52 UT makes a great choice for nighttime adventures.

- ◆ Tempered glass lens features double-sided anti-reflective coating
- ◆ Heat sink body design allows more efficient heat dissipation
- ◆ Reverse polarity for protection of the circuit board
- ◆ Lockout mode to prevent accidental triggering
- ◆ Red LED indicator above Micro-USB port glows when battery power is low








1111111

included

compatible

1.5 meters



LED headlamp with an output range of 2 to 500 lumens running off of a single CR123A or RCR123A battery. The H1 comes with a highly efficient CREE XM-L2 LED and TIR bead lens for maximum clarity. The focus and the flood are clearly divided, yet the area between the two is a smooth transition. The lightweight H1 is extremely small mimicking the size of an adult thumb. The light is connected to the head strap through a silicone mount, and can freely rotate to adjust the beam angle. After removing the light from the mount, attach the provided pocket clip and it can easily turn into a standard pocket flashlight with a magnetic tailcap. This high-output and convenient headlamp is an essential illumination tool for all activities in the dark.

* Optional green and orange head straps available




1600mAh CR123A

(L) 2.3in / 58.5mm× (D) 0.8in / 21mm

2.35 oz / 66.5 g (including battery)

CR123A or RCR123A






NEW

H1R NOVA RECHARGEABLE TOGETHER WITH YOUR PHONE

FEATURES

- Rechargeable via the magnetic tailcap
- Powered by a customized 650mAh rechargeable RCR123A battery with a maximum output up to 600 lumens
- Both cool white (5500K-7000K) and neutral white (4750K-5000K) LED versions available
- Compact and handy light with multiple use options: headlamp, pocket light, clip to a bag, etc.
- Olight USB magnetic charging cable included (compatible with S1R/S2R/S10RIII/S30RIII)
- 180 degrees smooth vertical rotation for the light on the silicone mount
- Bead optic lens for ideal close-range illumination






H1R NOVA

HIR NOVA

RECHARGEABLE & DETACHABLE LED HEADLAMP



STANDARD	MODE 1	MODE	2	MODE 3	MODE 4	MODE 5
314	600~180 lm	180 lr	n	60 lm	15 lm	2 lm
(1)	3+80 min	100 min		5 hrs	20 hrs	6 days
mm.	included	Cust		ustomized 650mAh RCR123		
	also comp	atible	Other RCR123A (not directly rechargeable)			
=	1.5 meters					
шшш	(L) 2.4in / 61.5mm× (D) 0.8in / 21mm 1.82 oz / 51.5 g (including battery)					
1						



DESCRIPTION

The H1R Nova (NW/CW) is the brighter and rechargeable version of the popular H1 Nova . Using a highly efficient CREE XM-L2 LED and TIR bead lens, the brightness covers a range of 2~600 lumens. Featuring a magnetic charging port, the light can be charged on the go with the included RCR123A battery and custom magnetic USB cable. With the included pocket clip and headband, the rechargeable H1R Nova can be used as a standard pocket light or headlamp making this one of the most practical and useful flashlights in the illumination industry.



MAX. 600 LUMENS










20mm Nylon Woven Headlamp Strap

150 LUMENS

Silicone Gel Button

HO5 ACTIVE

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT






DESCRIPTION

The H05 Active is a compact and lightweight LED headlamp powered by two AAA batteries. It uses a Cree XM-L2 LED featuring a high light transmission rate TIR optic lens that delivers an output of 10-150 lumens to fulfill the demand of close range illumination.

FEATURES

- ◆ Uses TIR optic lens, giving a soft and balanced beam
- ◆ Two red LED indicators for showing user location
- ◆ Stylish and fashionable design with multiple color choices





LET THERE BE LIGHT

BECAUSE THERE IS SO MUCH TO SEE IN THE DARK

MARKET APPLICATIONS

Outdoors













HO5S ACTIVE

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT

200 LUMENS

DESCRIPTION

The H05S Active is quite similar to its brother, H05 Active in structure and functions, yet with added features in built-in infrared motion sensor and a lower power indicator, and a maximum output of 200 lumens (50 lumens higher than H05). Also it only has black version, with no multiple color choices available.

FEATURES

- ◆ Uses TIR optic lens, giving soft and balanced beam
- ◆ Two red LED indicators for showing user location, and a low power indicator on the bottom of the lamp
- ◆ Hands free on/off control with built-in motion sensor



STANDARD	MODE 1		MODE 2	MODE 3		
31/2	200~120 lm		30 lm	10 lm		
2*AAA (1.5V Lithium Iron Battery)	10+200 min		8.5 hrs	24 hrs		
2*AAA (1.5V Alkaline Battery)	10+120 min		6 hrs	20 hrs		
	included		Customized 1.5V Lithium Iron AAA x 2			
	compatible AAA×2 (L) 2.2in / 56mm× (W) 1.4in / 36mm × (H) 1.4in / 36mm					
272	2.36 oz / 67	2.36 oz / 67 g (including battery)				



Four adjustable light angles including 10, 25, 35, 50 degrees below horizontal



Red Signal Light Indicating the Direction for Inserting the Batteries

250 LUMENS

STANDARD	MODE 1		MODE 2	MODE 3	
Diffuser OFF	250 lm		100 lm	15 lm	
Diffuser ON	200 lm		85 lm	12 lm	
	3 hrs		5.6 hrs	36 hrs	
шт	included	120	200mAh Rechargeable Lipo battery		
Ш	compatible Lipo battery or AAA × 4				
шшш	(L) 2.16in / 55mm× (W)1.06in / 27mm ×(H)1.65in / 42 mm (light head)				
	3.95 oz / 112 g (including battery)				



H15S WAVE

RECHARGEABLE VARIABLE-OUTPUT HEADLAMP

DESCRIPTION

The H15S Wave is a powerful and intelligent headlamp with a rechargeable battery pack and flip down diffuser. With 250 lumens of white light, three brightness levels and up to 36 hours of runtime, it is the perfect choice when you need hands free

- ◆ Diffuser for soft beam and improved close-range illumination
- ◆ Hand free on/off control with built-in motion sensor
- ◆ Light angle adjustable for 75 degrees
- ◆ Rechargeable through Micro-USB charging port





OLIGHT PRODUCT CATALOG









EXTENDED-RANGE VARIABLE-OUTPUT LED FLASHLIGHT



DESCRIPTION

The M23 Javelot is a tactical LED flashlight featuring a high intensity output with a compact form factor. The M23 Javelot features a customized CREE XP-L HI LED that reaches a maximum beam distance of 436 meters and has a maximum output of 1020 lumens. The M23 Javelot features a stainless steel bezel and a tail conductive structure that makes it more stable, durable and impact resistance.

STANDARD MODE 1 MODE 2 MODE 3 1020~600 lm 350 lm 20 lm (1) 5+55 min 2 hrs 30 hrs 18650 or 2 x CR123A (not included) compatible 1.5 meters (L) 5.71in / 145mm× (D) 1.61in / 41mm 5.36 oz / 152g (excluding battery)

FEATURES

- Customized LED with a tightly focused beam providing a 436-meter beam distance
- Reverse polarity protection to prevent improper battery
- Flush tailcap design enables the flashlight to stand with the bezel facing upwards
- Heat sink rings on the head for efficient heat dissipation



MARKET APPLICATIONS

FARTHER THROW DISTANCE

EXPERIENCE AN EXTENDED RANGE

Hunting Law Enforcement Self Defense Tactical

OLIGHT



















M1X STRIKER

VARIABLE-OUTPUT DUAL-SWITCH LED FLASHLIGHT

1000 LUMENS

DESCRIPTION

With a 1000-lumen strobe mode paired with a 1/2" striker bezel, this tool is the ultimate flashlight for self-defense. The tactical tail switch and a 1000-lumen turbo mode make this a perfect option for a powerful yet affordable light that you can depend on.

FEATURES

- ◆ Aggressive bezel
- ◆ Simple user interface
- ◆ Tempered glass lens of 99% light transmission rate with twosided, anti-reflective coating
- ◆ Reverse polarity protection to prevent improper battery installation



STANDARD	MODE 1	MODE 2	MODE 3	MODE 4	MODE 5	
314	1000~500 lm	350 lm	60 lm	10 lm	0.5 lm	
(1)	5+55 min	2 hrs	12 hrs	60 hrs	360 hrs	
compatible	18650 or 2 x CR123A (not included)					
=\=	1.5 meters					
шшш	(L) 5.35in / 136mm × (D) 1.02in / 26mm					
1	2.8 oz / 80g (excluding battery)					



1020 LUMENS

M2X-UT JAVELOT EXTENDED-RANGE VARIABLE-OUTPUT LED FLASHLIGHT

STANDARD	MODE 1	MODE 2	MODE 3			
314	1020 lm	250 lm	20 lm			
(1)	1 hr	3 hrs	30 hrs			
compatible	18650 or 2 x CF	18650 or 2 x CR123A (not included)				
!	1 meter					
шшш	n / 63mm					
272	7.69 oz / 218g (excluding battery)					



Flashlight mount, filters, and a remote pressure switch.

Optional Tactical Accessories

Ideal for hunting, law enforcement, search and rescue, outdoors, etc.



Red Filter



Blue Filter



The M2X-UT Javelot is a portable, extended-range LED flashlight with a beam that reaches out to 810 meters (2657 ft). With its CREE XP-L HI LED, the M2X-UT Javelot delivers a tightly focused 1020-lumen beam, making it ideal for longrange use.

FEATURES

DESCRIPTION

- Easy user interface, change modes by rotating the head
- Reverse polarity protection to prevent improper battery installation
- ◆ Intelligent temperature control system to prevent overheating
- ◆ Toughened ultra-clear mineral glass with anti-scratch coating ◆ Design of the tailcap enables the flashlight to stand with the
- bezel facing upwards















M3XS-UT JAVELOT

EXTENDED-RANGE VARIABLE-OUTPUT DUAL-SWITCH LED FLASHLIGHT



DESCRIPTION

With a beam distance of 1,000 meters and featuring a large reflector and dedomed CREE XP-L HI LED, the M3XS-UT is by far the longest beam distance light produced by Olight. This is the perfect light for long distance applications such as search and rescue.

FEATURES

- ◆ Easy user interface
- Reverse polarity protection to prevent improper battery installation
- ◆ Tempered glass lens of 99% light transmission rate with twosided, anti-reflective coating
- Design of the tailcap enables the flashlight to stand with the bezel facing upwards
- ◆ Battery power indicator under the side switch



STANDARD	MODE 1	MODE 2	MODE 3	MODE 4			
314	1200~720 lm	600 lm	80 lm	3 lm			
	5+55 min	1.5 hrs	12 hrs	360 hrs			
compatible	2 x 18650 or 3 x CR123A (not included)						
-V=	1 meter						
шшш	(L) 8.3in / 211mm × (D) 2.48in / 63mm 8.99 oz / 255g (excluding battery)						
$\overline{\Omega}$							



820 LUMENS

STANDARD	MODE 1	MODE 2	MODE 3		
314	820 lm	150 lm	25 lm		
(1)	1.25 hrs	3 hrs	18 hrs		
compatible	18650 or 2 x CR123A (not included)				
	1.5 meters (L) 5.51in / 140mm × (D) 1.4in / 35.5mm				
шш					
$\Delta \Gamma$	4.4 oz / 125g (excluding battery)				

M20SX Hunting Kit

M20SX Javelot HUNTING KIT includes the M20SX light, weapon mount, pressure switch, and red, green, and blue filters.











M20SX JAVELOT

VARIABLE-OUTPUT DUAL-SWITCH LED FLASHLIGHT

DESCRIPTION

The M20SX Javelot is a new generation of our signature dual tailcap switch tactical lights. The maximum output has been improved to 820 lumens. The LED lamp has been customized to produce a light range up to 370 meters.

- ◆ Instant access to strobe through side tailcap switch
- Customized LED with tightly focused beam delivering 370 meters of distance
- ♦ Reverse polarity protection to prevent improper battery installation
- ◆ Easily accessible lockout function with a half turn of the tailcap



NEVERENDING GREAT ILLUMINATION CONVENIENT RECHARGING R-SERIES MARKET APPLICATIONS Law Enforcement Search & Rescue Household Outdoors MAKING A **DIFFERENCE** | OLIGHTWORLD.COM





















R20 JAVELOT

VARIABLE-OUTPUT TAIL-SWITCH TACTICAL LED FLASHLIGHT



DESCRIPTION

The R20 Javelot is a compact rechargeable LED flashlight with a CREE XP-L HI LED that has a maximum output of 900 lumens and a beam distance of 314 meters. This model contains a high quality rechargeable 2600mAh 18650 battery and charges through a Micro-USB port on the neck of the flashlight for convenience. The R20 Javelot is the perfect companion for everyday personal or occupational use.

FEATURES

- ◆ CREE XP-L HI LED
- ◆ Smooth reflector with a double-sided anti-reflective hardened glass lens
- ◆ Micro-USB charging port on the neck of the flashlight using a protection ring for dustproof and waterproof capability
- ◆ Indication light above the USB charging port for battery low voltage warning




STANDARD	MODE 1	MODE 2	MODE 3			
314	900~450 lm	100 lm	10 lm			
(1)	3+150 min	9 hrs	80 hrs			
mm.	included	Customized 2600mAh 18650				
	also compatible	Other 18650 (not directly rechargeable)				
=	1.5 meters					
шшш	(L) 5.19in / 132mm × (D) 1.24in / 31.5mm					
$\overline{\mathbb{Q}}$	4.69 oz / 133g (including battery)					



2500 LUMENS

STANDARD	MODE 1	MODE 2		MODE 3	MODE 4	
31/4	2500~800 lm	120	00~800 lm	300 lm	50 lm	
(1)	2+150 min	12+130 min		6 hrs	50 hrs	
mm.	included Customize			zed 4500mAh 26650		
				650 battery tly rechargeable)		
=	1 meter (L) 5.24in / 133mm × (HD) 1.65in / 42mm × (BD) 1.26in / 32mm 8.99 oz / 255g (including battery)					
шшш						



R50 SEEKER

VARIABLE-OUTPUT SIDE SWITCH LED FLASHLIGHT

DESCRIPTION

The R50 Seeker is a USB rechargeable flashlight that delivers a maximum of 2500 lumens featuring a CREE XLamp XHP50 LED with an orange peel reflector for the perfect light combination of distance and width. With its included 26650 4500mAh rechargeable lithium battery and a compact micro-USB cable, the hand-sized R50 Seeker is easy to keep on hand, in your car, a backpack, or wherever you might need a light.

- ◆ Multi-function side switch with battery power indicator
- Stainless steel bezel and switch ring with blue PVD
- Micro-USB charging port

















Law Enforcement Kit







R50 PRO LE SEEKER

VARIABLE-OUTPUT SIDE SWITCH LED FLASHLIGHT

3200 LUMENS

DESCRIPTION

The R50 PRO LE (Law Enforcement) is a high-output, rechargeable side-switch LED flashlight that utilizes Olight's signature magnetic charging system built into a fast charging R Dock that can be installed in a car or at home. The R50 Pro LE holds a CREE XHP70 LED producing 3200 lumens that can take care of anything that the night holds.

FEATURES

- ♦ Built-in 3A fast charging circuit board to work with the R Dock. It can be charged up to 80% of full capacity with 1.5 hours
- Emergency use. When the R Dock was suddenly powered off, it can immediately turn on the flashlight under the low mode through infrared communication
- ◆ Convenient installation. With the installation kit provided, it can easily be mounted to and charged up in a vehicle or against a wall indoors



STANDARD	MODE 1	MODE 2		MODE 3	MODE 4	
31/2	3200~1000 lm	1500~1000 lm		400 lm	60 lm	
(1)	1.5+150 min	10+160 min		7.5 hrs	50 hrs	
	included	d Cu		Customized 4500mAh 26650		
<u> </u>	also compatible		Other 26650 battery (not directly rechargeable)			
=	1 meter					
шшш	(L) 5.04in / 128mm × (HD) 1.65in / 42mm × (BD) 1.26in / 32mm					
	9.24 oz / 262g (including battery)					







3200 LUMENS

STANDARD	MODE 1	МО	DE 2	MODE 3	MODE 4		
31/2	3200~1000 lm	150	00~1000 lm	400 lm	60 lm		
(1)	1.5+150 min	10	+160 min	7.5 hrs	50 hrs		
	included		Customized 4500mAh 26650				
<u> </u>	also compatible		Other 26650 battery (not directly rechargeable)				
=	1 meter (L) 5.04in / 128mm × (HD) 1.65in / 42mn × (BD) 1.26in / 32mm						
шш					2mm		
1	9.24 oz / 262g (including battery)						




R50 PRO SEEKER

VARIABLE-OUTPUT SIDE SWITCH LED FLASHLIGHT

DESCRIPTION

The R50 PRO is a high-output, rechargeable side-switch LED flashlight that utilizes Olight's signature magnetic charging system with an included USB cable that attaches to the back of the light. The R50 Pro holds a CREE XHP70 LED producing 3200 lumens perfect for home or on the go.

- ◆ Utilizing CREE XHP70 cool white LED; light output ranges from 60 to 3200 lumens
- ◆ Low power/lockout indicator under the side switch that glows red when the battery is running low or being hit under lockout
- Rechargeable through the magnetic charging cable provided with a charging current of 1A





NEW



Stainless Steel Quick-release Swing Arm Mount

PL-1 II VALKYRIE

LED WEAPONLIGHT



DESCRIPTION

Take control and shift the balance of power with Olight's new PL-1 II Valkyrie LED weaponlight. Easily engage the 450-lumen beam via its tactile ambidextrous switch to identify or disorientate an intruder with its strobe function. Change out the battery easily by unscrewing the bezel of the light and quickly attach the PL-1 II Valkyrie to your firearm's Picatinny or Glock style rail via its durable swing arm mount.

Having a weaponlight is essential to knowing your target in the dark, so make sure you get your hands on Olight's PL-1 II Valkyrie and defend what's yours.

STANDARD	WHITE LIGHT		STROBE						
31/2	450 lm		450 lm (10Hz)						
(1)	60 min		120 min						
Ш	included		CR123A battery						
шш	compatible	CR123A	or RCR123A						
=	1 meter								
шшш	(L) 3.07 inch/78mm × (W) 1.22 inch/31mm × (H) 1.49 inch/37.8mm								
717	3.95oz / 112	g (includi	ng battery)						


FEATURES

- ◆ Applicable on MIL-STD-1913 (Picatinny) and Glock sized rails
- Switch on/off silently
- ◆ Fast attach and release
- ◆ IPX 6 Waterproof
- ◆ Hardened glass with anti-reflective coating





Unscrew the bezel for easy access to the battery compartment





BUILT FOR FLASHLIGHT FANATICS!

THREE XHP70 LED'S **FOUR HDC 18650 BATTERIES** EXPERIENCE 9000 LUMENS OF UNPRECEDENTED ILLUMINATION! **X-SERIES**

MAX. TO TO TO LUMENS

MARKET APPLICATIONS

Search & Rescue Outdoors

OLIGHT

MAKING A **DIFFERENCE** | OLIGHTWORLD.COM

















Three Top-class CREE XHP 70 LED With A Total of 12 Light-emitting Cores.

X7 MARAUDER

VARIABLE-OUTPUT SIDE-SWITCH LED FLASHLIGHT



DESCRIPTION

Welcome to the X7 Marauder. Featuring 9000 lumens in a "soda can" sized light to provide the power of the sun in the palm of your hand. The X7 Marauder carries three four-core light-emitting XHP70 LED's which are currently one of the highest performing light sources on the planet. The light features a custom designed orange peel reflector to create the perfect beam pattern for logical and realistic use.

- ◆ Three top-class cool white CREE XHP70 LEDs with a total of 12 light-emitting cores
- ◆ Maximum output reaching 9000 lumens at turbo S mode
- ◆ Low battery indicator on the side of the flashlight body
- ♦ When powered by four Olight HDC 3500mAh 18650 batteries as provided in the kit, the X7 can reach the Turbo S mode of 9,000 lumens

STANDARD	TURBO S	TURBO	MODE 3	MODE 4	MODE 5	MODE 6							
31/2	*9000~1800 lm	5500~1800 lm	3000~1800 lm	1000 lm	300 lm	3 lm							
()	2.5+200 min	8+215 min	32+200 min	390 min	18 hrs	30 days							
	included * HDC 3500mAh 18650 Lithium Batteries x 4												
	also compatible 4x Other 18650, 8 x CR123A												
	1 meter												
111111	(L) 5in / 127mm×	(L) 5in / 127mm×(HD) 2.68in / 68mm ×(BD) 2.05in / 52mm											
272	16.6 oz / 471g (e	16.6 oz / 471g (excluding battery)											

^{*} It can be driven to the Turbo S mode with four Olight HDC 3500mAh 18650 batteries, or 18650 batteries with a discharging current of over 8A. Batteries are included for the kit only.







BATTERIES

Various batteries such as 18650, 16340, 14500, 26650, CR123A or lithium iron batteries that can be used to power your flashlights.



COLOR FILTERS/DIFFUSERS

Filters are available in different sizes to fit the S series, M series, and SR series flashlights.



TRAFFIC WAND / DIFFUSER WAND

Orange and white traffic wands to convert your S series, M series or R series flashlights into a glowing high-visibility flashlight.



WEAPON MOUNT

This weapon mount securely attaches your 1 inch bodied light to Picatinny and Weaver rails.




MAGNETIC WEAPON MOUNT

Easily attach a flashlight to weapons that do not have rails or other mounting options.



**** OMNI DOK**

An intelligent charger that can match any rechargeable batteries which can insert into the charge bays, such as AA/AAA NiMH batteries, 18650, 16340, 14500 lithium batteries, etc.





HOLSTER

Olight provides a holster for a number of flashlights for better protection of them. Also with a holster, users can attach a flashlight to their belt.



REMOTE PRESSURE SWITCH

Remote pressure switch allows you to activate your M series weapon lights while maintaining your preferred grip.



USB CHARGING DOCK (MICRO DOK)

It can charge rechargeable flashlights through a magnetic contact charging base. The new dock has three suction cups to increase its stability.



CAR CHARGER (INCLUDING USB CAR CHARGER)

This is to be used to charge some Olight flashlights either through a micro-USB port on the flashlight body, such as R20, R50 or through a charging dock, such as R50 PRO LE.



MAGNETIC CHARGING CABLE

This is the charging cable that works by attaching the magnetic end to the tailcap of the rechargeable S series flashlights.



*** UC**

This is a universal magnetic USB battery charger that can work with all single cylinder rechargeable batteries of various sizes, such as AA/ AAA NiMH batteries, 18650, 16340, 14500 lithium batteries, etc.



IMAGE	ACCESSORY	I3E EOS	S1 BATON	S2 BATON	S1A BATON	S2A BATON	S1R BATON	S2R BATON	S10R BATON III	S30R BATON III	SR MINI II (and Kit)	SR52 UT (and Kit)	H1 HOVA	H05 ACTIVE	H05S ACTIVE	H15S WAVE	M1X STRIKER	M2X-UT JAVELOT	M3XS-UT JAVELOT (and Kit)		M23 JAVELOT (and Kit)	R20 JAVELOT	R50 SEEKER	R50 PRO SEEKER	R50 PRO LE SEEKER	PL-1 II	X7 MARAUDER
	HOLSTER	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	√	√	N/A	N/A	N/A	N/A	N/A	√	√	\checkmark	√	N/A	*	√	√	N/A	√
9	MAGNETIC CHARGING CABLE	N/A	N/A	N/A	N/A	N/A	√	√	*	*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	√	N/A	N/A	N/A
	USB CHARGING DOCK (MICRO DOK)	N/A	N/A	N/A	N/A	N/A	*	*	√	√	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
65×	CAR CHARGER (INCLUDING USB CAR CHARGER)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	*		* (with kit)		N/A	N/A	N/A	*	N/A	N/A	N/A	N/A	N/A	*	N/A	N/A	\checkmark	N/A	N/A
	USB CABLE	N/A	N/A	N/A	N/A	N/A	N/A	N/A	√	√	√	\checkmark	N/A	N/A	N/A	\checkmark	N/A	N/A	N/A	N/A	N/A	\checkmark	\checkmark	N/A	N/A	N/A	N/A
o le	MAGNETIC WEAPON MOUNT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	*	*	*		* /(with kit)	N/A	N/A	N/A	N/A	N/A	N/A
Q _i	WEAPON MOUNT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	*	*	*	*	*	N/A	N/A	N/A	N/A	N/A	N/A
9	REMOTE PRESSURE SWITCH	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	*	*	*	*	*	N/A	N/A	N/A	N/A	N/A	N/A
	EXTENSION TUBE	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	*	\checkmark	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
A A	DIFFUSER WAND (TW1)	N/A	*	N/A	*	N/A	*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	DIFFUSER WAND (TW10)	N/A	N/A	*	N/A	*	N/A	*	*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	TRAFFIC WAND (TW50)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	*	N/A	N/A	*	*	*	N/A	N/A
00	COLOR FULTERS	N/A	N/A	N/A	N/A	N/A	N/A	N/A	*	*	N/A	*	N/A	N/A	N/A	N/A	*	*	*	*	√ *(with kit)	N/A	N/A	N/A	N/A	N/A	N/A

Accessory comes with the product or kit
Accessory compatible with, but does not come with the product or kit
Accessory not applicable for the product or kit

2017 FULL LINE PRODUCT CATALOG

PRODUCT	LED	CANDELA	TURBO S	TURBO	нідн	OUTPUT RUNTIME MEDIUM		MOONLIGHT/ NIGHTLIGHT	STROBE (10HZ)	WEIGHT (EXCLUDING BATTERIES)	BEAM DISTANCE	DIMENSION (L)×(D)	BATTERY	WATERPROOF
i3E EOS (Gift Box Edition)	LUXEON TX- L1T2	500 cd	/	/	90 lm 2 hrs	/	/	/	/	0.63 oz 17.9 g (including battery)	144 ft 44 m	2.38"*0.55" 60.5*14 mm	AAA √ 1.5V Lithium Iron AAA Battery	IPX8
S1 Baton	CREE XM-L2	3,000 cd	/	/	500~300 lm 1.5+90 min	80 lm 1 6 hrs	8 lm 1 40 hrs	0.5 lm 1 25 days	√	1.06 oz 30 g	361 ft 110 m	2.4"*0.83" 61*21mm	CR123A RCR123A	IPX8
S2 Baton	CREE XM-L2	5,000 cd	/	950~400 lm ② 2+170 min	400 lm 2 245 min	80 lm 2 19 hrs	10 lm 2 144 hrs	0.5 lm 2 60 days	√	1.78 oz 50.5 g	466 ft 142 m	4.06"*0.91" 103*23 mm	18650 2×CR123A / RCR123A	IPX8
S1A Baton	CREE XM-L2	3,480 cd	/	600 3 ~300 lm 1+60 min	220~100 lm 110+30 min	50 lm 10.5 hrs	5 lm 80 hrs	0.5 lm 25 days	√	1.85 oz 52.5 g (including battery)	387 ft 118 m	3.13"*0.83" 79.5*21 mm	AA ✓ 1.5V Lithium Iron AA Battery	IPX8
S2A Baton	CREE XM-L2	3,000 cd	/	550~260 lm 3+240 min	260 lm 250 min	120 lm 10 hrs	20 lm 80 hrs	0.5 lm 	\checkmark	3.03 oz 86 g (including battery)	361 ft 110 m	5.20"*0.91" 	2×AA √2×1.5V Lithium Iron AA Battery	IPX8
S1R Baton	CREE XM-L2	5,250 cd	900~300 lm 1.5+50 min	600~300 lm 1.5+55 min	300 lm 60 min	60 lm 4.5 hrs	12 lm 33 hrs	0.5 lm 15 days	√	1.9 oz 54 g (including battery)	476 ft 145 m	2.6"*0.83" 66*21 mm	RCR123A ✓ Customized 550mAh 5C RCR123A	IPX8
S2R Baton	CREE XM-L2	5,800 cd	/	1,020~500 lm 2+190 min	500 lm 200 min	120 lm 13 hrs	12 lm 120 hrs	0.5 lm 	\checkmark	3.58 oz 101.5 g (including battery)	502 ft 153 m	4.13"*0.91" 	18650 or 2×RCR123A ✓ Customized 3200mAh 18650 Battery	IPX8
S10R Baton III	LUMINUS SST-40	3,500 cd	/	/	600~300 lm 1.5+60 min	120 lm 160 min	12 lm 33 hrs	0.5 lm 15 days	√	2.05 oz 58 g (including battery)	387 ft 118 m	2.70"*0.91" 68.5*23 mm	RCR123A Customized 650mAh RCR123A	IPX8
S30R Baton III	CREE XM-L2	8,840 cd	/	1,050~500 lm 2+200 min	500 lm 210 min	120 lm 15 hrs	12 lm 130 hrs	0.5 lm 100 days	√	3.88 oz 110 g (including battery)	616 ft - 188 m	4.49"*0.98" 114*25 mm	18650 or 2×RCR123A ✓ Customized 3500mAh 18650 Battery	IPX8
SR MINI Intimidator II	CREE XM-L2*3	18,000 cd	/	3,200 lm	1,600 lm 3 hrs	600 lm 8 hrs	120 lm 36 hrs	/	\checkmark	6.38 oz 	879 ft 268 m	5.2"*1.87" 	3×18650 	IPX8
SR 52UT Intimidator	CREE XP-L HI	160,000 cd	/	/	1,100 lm 4 hrs	550 lm 7.5 hrs	80 lm 40 hrs	/	\checkmark	14.3 oz 405 g	2,625 ft 800 m	6.3"*2.48" 161.5*63 mm	3×18650 6×CR123A	IPX8
H1 Nova	CREE XM-L2	1,080 cd	/	500~180 lm 3+170 min	180 lm 3 hrs	60 lm 8.5 hrs	15 lm 	2 lm 15 days	/	2.35 oz 66.5 g (including battery)	217 ft 66 m	2.3"*0.8" 58.5*21 mm	CR123A or RCR123A √ 3V 1600mAh CR123A	IPX8
H1R Nova	CREE XM-L2	1,280 cd	/	600~180 lm 3+80 min	180 lm 100 min	60 lm 5 hrs	15 lm 20 hrs	2 lm 6 days	/	1.82 oz 51.5 g (including battery)	236 ft 72 m	2.4"*0.8" 61.5*21 mm	RCR123A Customized 650mAh RCR123A	IPX8

✓ Product comes with battery as described


The specified runtime is reached when using a single 3V 1500mAh CR123A.
 The specified runtime is reached when using a single 3.6V 3400mAh 18650.
 Maximum output of 600 lumens for S1A is achievable when 14500 rechargeable lithium battery is used


- 2017 FULL LINE PRODUCT CATALOG

PRODUCT LED		CANDELA				OUTPUT RUNTIME			STROBE		BEAM	DIMENSION	BATTERY	WATERPROOF
rkoboci		CANDLLA	TURBOS TURBO HIGH MEDIUM LOW MOONLIG	MOONLIGHT/ NIGHTLIGHT	(10HZ)	(EXCLUDING BATTERIES)	DISTANCE	(L)×(D)	BATTERI	WATER ROOF				
H05 Active	CREE XM-L2	750 cd	/	/	150~90 lm 10+280 min	30 lm 10 hrs	10 lm 40 hrs	/	/	2.24 oz 63.5 g (including battery)	180 ft 55 m	2.2"*1.34"*1.41" 56*34*36 mm	2x AAA √ 2×1.5V Lithium Iron AAA Battery	IPX4
H05S Active	CREE XM-L2	900 cd	/	/	200~120 lm 10+200 min	30 lm 8.5 hrs	10 lm 24 hrs	/	/	2.36 oz 67 g (including battery)	197 ft 60 m	2.2"*1.4"*1.4" 56*36*36 mm	2 x AAA √ 2×1.5V Lithium Iron AAA Battery	IPX4
H15S Wave	CREE XM-L2	1,805 cd	/	/	250 lm 3 hrs	100 lm 5.6 hrs	15 lm 36 hrs	/	/	3.95 oz 112 g (including battery)	279 ft 	2.16"*1.06"*1.65" - 55*27* 42mm	Lipo battery or AAA x 4 √ 1200 mAh Rechargeable Lipo Battery	IPX6
M1X Striker	CREE XM-L2	9,000 cd	/	1,000~500 lm 5+55 min	350 lm 2 hrs	60 lm 12 hrs	10 lm 60 hrs	0.5 lm 360 hrs	√	2.8 oz 80 g	623 ft 190 m	5.35"*1.02" 136*26 mm	2×CR123A 18650	IPX8
M2X-UT Javelot	CREE XP-L HI	164,000 cd	/	/	1,020 lm 1 hr	250 lm 3 hrs	20 lm 30 hrs	/	\checkmark	7.69 oz 218 g	2,657 ft 810 m	6.41"*2.48" 163*63 mm	2×CR123A 18650	IPX8
M3XS-UT Javelot	CREE XP-L HI	250,000 cd	/	1,200~720 lm 5+55 min	600 lm 1.5 hrs	80 lm 12 hrs	3 lm 360 hrs	/	\checkmark	8.99 oz 	3,281 f t 1000 m	8.3"*2.48" 211*63 mm	2×18650 or 3 x CR123A √ 2×3600mAh 18650 Batteries (for the kit only)	IPX8
M20SX Javelot	CREE XM-L2	34,200 cd	/	/	820 lm 1.25 hrs	150 lm 3 hrs	25 lm 18 hrs	/	\checkmark	4.4 oz 125 g	1,214 ft 370 m	5.51"*1.4" 140*35.5 mm	2 x CR123A 18650	IPX7
M23 Javelot	CREE XP-L HI	47,500 cd	/	/	1020~600 lm 5+55 min	350 lm 2 hrs	20 lm 30 hrs	/	\checkmark	5.36 oz 152 g	1,430 f t 436 m	5.71"*1.61" 145*41 mm	2 x CR123A 18650	IPX8
R20 Javelot	CREE XP-L HI	24,700 cd	/	/	900~450 lm 3+150 min	100 lm 9 hrs	10 lm 80 hrs	/	/	4.69 oz 133 g (including battery)	1,030 ft 314 m	5.19"*1.24" 132*31.5 mm	18650 ✓ Customized 2600mAh 18650 Battery	IPX8
R50 Seeker	CREE XHP50	22,000 cd	/	2,500~800 lm 	1,200~800 lm 12+130 min	300 lm 6 hrs	50 lm 50 hrs	/	\checkmark	8.99 oz 255 g (including battery)	974 ft 297 m	5.24"*1.65" 133*42 mm	26650 ✓ Customized 4500mAh 26650 Battery	IPX8
R50 PRO/ LE Seeker	CREE XHP70	15,600 cd	/	3,200~1,000 lm 1.5+150 min	1,500~1,000 lm 10+160 min	400 lm 7.5 hrs	60 lm 50 hrs	/	√	9.24 oz 262 g (including battery)	820 ft 250 m	5.04"*1.65" 128*42 mm	26650 ✓ Customized 4500mAh 26650 Battery	IPX8
PL-1 II Valkyrie	CREE XP-L	2,800 cd	/	/	/	450 lm 60 min	/	/	√	3.95 oz 112 g (including battery)	348 ft 106 m	3.07"*1.22"*1.49" 78*31*37.8 mm	CR123A or RCR123A √ 3V 1600mAh CR123A Battery	IPX6
X7 Marauder	CREE XHP70*3	24,500 cd	9,000 4 ~1,800 lm 2.5+200 min	5,500~1,800 lm 8+215 min	3,000~1,800 lm 32+200 min	1,000 lm 390 min	300 lm 18 hrs	3 lm 30 days	√	16.6 oz 471 g	1,027 ft 313 m	5"*2.68" 127*68 mm	4 x 18650 or 8 x CR123A √ 4 x HDC 3500mAh 18650 Batteries (for the kit	IPX8 t only)

⁴ Maximum output of 9000 lumens is achievable when four 18650 batteries with a discharging current of over 8A each (including Olight HDC 3500mAh 18650 batteries) are used

✓ Product comes with battery as described









OUR WARRANTY

Here at Olight, we believe in our products.

If your Olight product has any defect as the result of the materials or workmanship we want to make it right!

Within 30 days of purchase: Return the product to the retailer you purchased it from and they will replace or repair it. Period.

Within 5 years of purchase: Return the product to Olight and we will repair or replace it as long as the light is not working because of factory defects. This does not include obvious user wear or extreme damage.

After 5 years of purchase: Return the product to Olight and we will repair or replace it. We will assess the fees involved and will let you know once we receive it.

The Omni Dok is also under Olight's 5 year warranty.

Of course, this warranty does not cover normal wear and tear. IF YOUR LIGHT HAS SIGNIFICANT DAMAGE AND IT IS SENT TO US, WE WILL SEND IT BACK TO YOU. This warranty also does NOT cover modifications, misuse, disintegrations, negligence, accidents, improper maintenance, or repair by anyone other than an Authorized retailer or Olight itself. BUYER IS RESPONSIBLE FOR RETURN SHIPPING COSTS. Please note that the warranty process may take 3-4 weeks to get it back to you.

*Accessories such as pocket clips, holsters, and charging cables are not under the 5 year warranty. These are accessories given for free with our products.

The H15 and H15S Wave are currently under a 2 year warranty.

Batteries are currently under a 1 year warranty.





olightworld.com
All performance is tested based on ANSI/NEMA
FL1-2009 Standards.
Made in China.
© Olight 01/01/17 V1

MAKING A **DIFFERENCE** | OLIGHTWORLD.COM



DISCLAIMER

Olight tries to ensure that all of the information herein is accurate, complete and current. However, there may be instances when information about an item contains inaccurate or incomplete data, including data about the item's price or availability, due to a typographical or other error.

Any features and specifications that may be referenced herein are subject to change at any time without notice. Weights and measurement are approximate. Olight does not guarantee that product images, if applicable, are represented with perfect accuracy. Variations in color, size, and other specifications or features may occur. Other product limitations and disclaims may apply.

OLIGHT DISCLAIMS ALL WARRANTIES, WHETHER EXPRESS OR IMPLIED. WITH RESPECT TO THE ACCURACY OR COMPLETENESS OF ANY INFORMATION CONTAINED HEREIN, TO THE FULLEST POSSIBLE UNDER APPLICATION LAWS. UNDER NO CIRCUMSTANCES SHALL OLIGHT BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES THAT RESULT FROM YOUR RELIANCE ON ANY INFORMATION CONTAINED HEREIN, EVEN IF OLIGHT HAS BEEN ADVISED OF OR SHOULD HAVE KNOWLEDGE OF THE POSSIBILITY OF SUCH DAMAGES.